



BECK MANUFACTURING
 330 East Ninth Street
 P. O. Box 510
 Waynesboro, PA 17268

Tel: 717-762-9141
 Fax: 717-762-6550

CERTIFICATE OF COMPLIANCE

OUR ORDER NO. _____ DATE _____

SOLD TO _____ ITEM _____

To Whom It May Concern:

Pressure – Temperature Ratings of our hex bushings, solid plugs, face bushings and caps are as follows:

Temperature Degrees F	Pressure PSIG		
	Bushing Caps	Plugs	Face Bushings
-20 to 150	300	2000	2000
200	265	1785	1785
250	225	1575	1575
300	185	1360	1360
350*	150	1150	1150

*Permissible for Service Temperature up to 366 degree F, reflecting the temperature of saturated steam at 150 PSIG.

Our threading is in accordance with American National Standard for Pipe Threads (ANSI B1.20.1).

All internal threads are countersunk a distance of not less than one half the pitch of the thread at an angle of approximately 45 degree with the axis of the thread.

All plugs are threaded with American National Standard Taper Pipe Threads. The variation in threading is limited to one turn large or one turn small from the gaging notch on plug and gaging face of ring using working gages.

Sincerely,

Dale E. Thompson
 Quality Manager

**UNCONTROLLED
 COPY**