

Cap  
Fig. SK-1



Material Specifications

**Cast Fittings**  
Ductile Iron conforming to ASTM A536


**Coatings**  
Rust inhibiting paint  
Color: Orange (standard)  
Hot Dipped Zinc Galvanized  
conforming to ASTM A153 (optional)  
Other available options  
Example: RAL3000 or RAL9000 Series

For Listings/Approval Details and Limitations, visit our website at [www.asc-es.com](http://www.asc-es.com) or contact an ASC Engineered Solutions™ Sales Representative.



PROJECT INFORMATION		APPROVAL STAMP
Project:		Approved
Address:		Approved as noted
Contractor:		Not approved
Engineer:		Remarks:
Submittal Date:		
Notes 1:		
Notes 2:		

## Cap Fig. SK-1



Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./kg
1¼ 32	1.660 42.2	1 25	0.4 0.2
1½ 40	1.900 48.3	1 25	0.5 0.2
2 50	2.375 60.3	1 25	0.7 0.3
2½ 65	2.875 73.0	1 25	1.0 0.4
3 80	3.500 88.9	1 25	1.5 0.7
4 100	4.500 114.3	1½/₁₆ 27	2.7 1.2
5 125	5.563 141.3	1½/₁₆ 27	4.4 2.0
6 150	6.625 168.3	1½/₁₆ 27	6.6 3.0
8 200	8.625 219.1	1¾/₁₆ 30	11.3 5.1
10* 250	10.750 273.1	1¼ 32	21.0 9.5
12* 300	12.750 323.9	1¼ 32	35.5 16.1

**Note:**

\*Supplied as Style K-1 only.



asc-es.com

Building connections that last™