SPF/Anvil® Grooved Fittings





Material Specifications

Cast Fittings

Ductile Iron conforming to ASTM A536

Coatings

Rust inhibiting paint Color: Orange (standard) Hot Dipped Zinc Galvanized conforming to ASTM A153 (optional) Other available options

Example: RAL3000 or RAL9000 Series

For Listings/Approval Details and Limitations, visit our website at www.asc-es.com or contact an ASC Engineered Solutions $^{\text{\tiny TM}}$ Sales Representative.




PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	

SPF/Anvil® Grooved Fittings



Straight Tee **Fig. T-1**



Nominal Size	0.D.	Center to End	Approx. Wt. Ea.	Nominal Size	0.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./kg	In./DN(mm)	In./mm	ln./mm	Lbs./kg
1	1.315	2 1/4	0.9	4	4.500	5	9.6
25	33.4	57	0.4	100	114.3	127	4.4
1 1/4	1.660	23/4	1.4	5	5.563	51/2	17.8
32	42.2	69	0.7	125	141.3	140	8.1
1 1/2	1.900	23/4	1.5	6	6.625	61/2	25.3
40	48.3	69	0.7	150	168.3	165	11.5
2	2.375	3 1/4	2.4	8	8.625	73/4	42.1
50	60.3	83	1.1	200	219.1	197	19.1
21/2	2.875	33/4	3.6	10	10.750	9	69.0
65	73.0	95	1.6	250	273.1	229	31.3
3	3.500	4 1/4	6.3	12	12.750	10	91.0
80	88.9	108	2.9	300	323.9	254	41.3



asc-es.com