

AS 733     EG,  GR

### 6-HOLE "U" SUPPORT

Use with AS 200 & AS 210  
Std Pkg 10 - Wt./100 pcs: 167 Lbs.

AS 735     EG,  GR

### 8-HOLE "U" SUPPORT

Use with AS 200 BTB  
Std Pkg 10 - Wt./100 pcs: 266 Lbs.

AS 687     EG,  GR

### SLOTTED "U" SUPPORT

Catalog No.	A	B	Wt./100 Pcs.
AS 687 A	7 1/4"	4 1/8"	103
AS 687 B	8 1/2"	5 3/8"	115
AS 687 C	10 3/8"	7 1/4"	135

Use with AS 200 & AS 210  
Std Pkg 10 - Wt./100 pcs: See chart above.

AS 677     EG,  GR

### CUP SUPPORT FOR STANDARD SINGLE STRUT

Use with AS 200 & AS 210  
Std Pkg 25 - Wt./100 pcs: 88 Lbs.

Page notes unless otherwise specified: 1/4" thick, 1 5/8" wide, holes 9/16" diameter, spaced 1 7/8" on center and 1 3/16" from end.

**LEGEND:**

GR: Powder Coated Supr-Green    EG: Electro-Galvanized    PG: Pre-Galvanized    AL: Aluminum    HG: Hot Dipped Galvanized    PL: Plain    SS: Stainless Steel    ZTC: Zinc Trivalent Chromium  
Stainless Steel (SS), Zinc Trivalent Chromium (ZTC) and Hot Dipped Galvanized (HG) are specialty finishes. Pricing is located in the Specialty Strut Section of the Anvil-Strut price book.

PROJECT INFORMATION		APPROVAL STAMP
Project:		<input type="checkbox"/> Approved
Address:		<input type="checkbox"/> Approved as noted
Contractor:		<input type="checkbox"/> Not approved
Engineer:		Remarks:
Submittal Date:		
Notes 1:		
Notes 2:		