



FIG. 7050DR 90° Drain Elbow



Drain elbow has a standard 1" female NPT outlet.



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

- Available galvanized.

Available fabricated Schedule 10 only.

FIGURE 7050DR 90° DRAIN ELBOW

Nominal Size	O.D.	Max. Working Pressure	Dimensions		Approx. Wt. Ea.
			Center to End	H	
In./DN(mm)	In./mm	PSI/bar	In./mm	In./mm	Lbs./Kg
1¼ 32	1.660 42.2	300 20.7	2¾ 70	1¾ 44	0.7 0.3
1½ 40	1.900 48.3	300 20.7	2¾ 70	1¾ 44	1.7 0.8
2 50	2.375 60.3	300 20.7	3¼ 83	1¾ 44	2.0 0.9
2½ 65	2.875 73.0	300 20.7	3¾ 95	1⅞ 48	2.5 1.1
3 80	3.500 88.9	300 20.7	4¼ 108	2 51	3.2 1.5
4 100	4.500 114.3	300 20.7	5 127	2¼ 57	4.6 2.1
5 125	5.563 141.3	300 20.7	5½ 140	2⅝ 60	11.5 5.2
6 150	6.625 168.3	300 20.7	6½ 165	2⅝ 60	9.6 4.4
8 200	8.625 219.1	300 20.7	7¾ 197	2½ 64	15.8 7.2
10 250	10.750 273.1	300 20.7	9 229	2¾ 69	48.5 22
12 300	12.750 323.9	300 20.7	10 254	2¾ 69	66 29

Additional sizes available, see Gruvlok Catalog or contact an Anvil Representative.

MATERIAL SPECIFICATIONS

FABRICATED FITTINGS:

1¼" - 6" are Carbon Steel, A-135, Schedule 10
8" - 12" are Carbon Steel, A-795/A-135/.188 Wall

COATINGS:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	