


# FIG. 7050S\*

# Standard 90° Elbow for Fire Protection



## FIGURE 7050S\* STANDARD 90° ELBOW

Nominal Size	O.D.	Max. Rated Pressure	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	Lbs./Kg
1	1.315	300	2¼	0.6
25	33.4	20.7	57	0.3
1¼	1.660	300	2¾	1.0
32	42.2	20.7	70	0.5
1½	1.900	300	2¾	1.2
40	48.3	20.7	70	0.5
2	2.375	300	3¼	1.7
50	60.3	20.7	83	0.8
2½	2.875	300	3¾	2.6
65	73.0	20.7	95	1.2
3 O.D.	2.996	300	4	3.6
76.1	76.1	20.7	102	1.6
3	3.500	300	4¼	4.0
80	88.9	20.7	108	1.8
4	4.500	300	5	7.7
100	114.3	20.7	127	3.5
5½ O.D.	5.500	300	5¼	10.9
139.7	139.7	20.7	133	4.9
5	5.563	300	5½	11.1
125	141.3	20.7	140	5.0
6½ O.D.	6.500	300	6½	17.4
165.1	165.1	20.7	165	7.9
6	6.625	300	6½	16.5
150	168.3	20.7	165	7.5
8	8.625	300	7¾	30.6
200	219.1	20.7	197	13.9
10	10.750	300	9	53.5
250	273.1	20.7	229	24.3
12	12.750	300	10	82
300	323.9	20.7	254	37.2

For additional sizes, see Fig. 7050 in the Gruvlok Catalog or contact an Anvil Representative.

These fittings are designed to provide minimal pressure drop and uniform strength.



- Available galvanized.

\* When ordering, refer to product as FP7050S.

## MATERIAL SPECIFICATIONS

### CAST FITTINGS:

Ductile Iron conforming to ASTM A-536

### COATINGS:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

## PROJECT INFORMATION

## APPROVAL STAMP

<b>Project:</b>	<input type="checkbox"/> Approved
<b>Address:</b>	<input type="checkbox"/> Approved as noted
<b>Contractor:</b>	<input type="checkbox"/> Not approved
<b>Engineer:</b>	<b>Remarks:</b>
<b>Submittal Date:</b>	
<b>Notes 1:</b>	
<b>Notes 2:</b>	