


FIG. 7051 *

Standard 45° Elbow for Fire Protection



**FIGURE 7051 *
STANDARD 45° ELBOW**

Nominal Size	O.D.	Max. Rated Pressure	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	Lbs./Kg
1¼ 32	1.660 42.2	300 20.7	1¾ 44	0.7 0.3
1½ 40	1.900 48.3	300 20.7	1¾ 44	0.9 0.4
2 50	2.375 60.3	300 20.7	2 51	1.5 0.7
2½ 65	2.875 73.0	300 20.7	2¼ 57	1.9 0.9
3 80	3.500 88.9	300 20.7	2½ 64	3.3 1.5
4 100	4.500 114.3	300 20.7	3 76	5.4 2.4
5 125	5.563 141.3	300 20.7	3¼ 83	9.0 4.1
6 150	6.625 168.3	300 20.7	3½ 89	11.2 5.1
8 200	8.625 219.1	300 20.7	4¼ 108	19.8 9.0

Additional sizes available, see Gruvlok Catalog or contact an Anvil Representative.

These fittings are designed to provide minimal pressure drop and uniform strength.



Available as a fabricated fitting.

- Available galvanized.

* When ordering, refer to product as FP7051.

For Listings/Approval Details and Limitations, visit our website at www.anvilint.com or contact an Anvil® Sales Representative.

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile Iron conforming to ASTM A-536

COATINGS:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	