


# FIG. 7076 Reducer Threaded



**FIGURE 7076 CONCENTRIC REDUCER (GROOVE BY THREAD)**

Nominal Size	O.D.-1	O.D.-2	End to End	Approx. Wt. Ea.	Nominal Size	O.D.-1	O.D.-2	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	In./mm	Lbs./Kg	In./DN(mm)	In./mm	In./mm	In./mm	Lbs./Kg
1½ x 1 40 x 25	1.900 48.3	1.315 33.4	2½ 64	0.6 0.3	4 x 1¼ 100 x 32	4.500 114.3	1.660 42.2	3 76	2.2 1.0
2 x ¾ 50 x 80	2.375 60.3	1.050 26.7	2½ 64	1.0 0.5	4 x 1½ 100 x 40	4.500 114.3	1.900 48.3	3 76	2.3 1.0
2 x 1 50 x 25	2.375 60.3	1.315 33.4	2½ 64	0.8 0.4	4 x 2 100 x 50	4.500 114.3	2.375 60.3	3 76	2.3 1.0
2 x 1¼ 50 x 32	2.375 60.3	1.660 42.2	2½ 64	1.3 0.6	4 x 2½ 100 x 65	4.500 114.3	2.875 73.0	3 76	2.3 1.0
2 x 1½ 50 x 40	2.375 60.3	1.900 48.3	2½ 64	1.3 0.6	4 x 3 100 x 80	4.500 114.3	3.500 88.9	3 76	2.6 1.2
2½ x 1 65 x 25	2.875 73.0	1.315 33.4	2½ 64	1.0 0.5	5 x 4 125 x 100	5.563 141.3	4.500 114.3	3½ 89	4.5 2.0
2½ x 1¼ 65 x 32	2.875 73.0	1.660 42.2	2½ 64	1.0 0.5	6 x 1 150 x 25	6.625 168.3	1.315 33.4	4 102	6.0 2.7
2½ x 1½ 65 x 40	2.875 73.0	1.900 48.3	2½ 64	1.3 0.6	6 x 1½ 150 x 40	6.625 168.3	1.900 48.3	4 102	6.1 2.8
2½ x 2 65 x 50	2.875 73.0	2.375 60.3	2½ 64	1.2 0.5	6 x 2 150 x 50	6.625 168.3	2.375 60.3	4 102	6.0 2.7
3 x ¾ 80 x 80	3.500 88.9	1.050 26.7	2½ 64	1.2 0.5	6 x 3 150 x 80	6.625 168.3	3.500 88.9	4 102	6.0 2.7
3 x 1 80 x 25	3.500 88.9	1.315 33.4	2½ 64	1.2 0.5	6 x 4 150 x 100	6.625 168.3	4.500 114.3	4 102	5.9 2.7
3 x 1¼ 80 x 32	3.500 88.9	1.660 42.2	2½ 64	1.3 0.6	6 x 5 150 x 125	6.625 168.3	5.563 141.3	4 102	5.8 2.6
3 x 1½ 80 x 40	3.500 88.9	1.900 48.3	2½ 64	1.3 0.6	8 x 3 200 x 80	8.625 219.1	3.500 88.9	3 76	9.3 4.2
3 x 2 80 x 50	3.500 88.9	2.375 60.3	2½ 64	1.3 0.6	8 x 4 200 x 100	8.625 219.1	4.500 114.3	3 76	10.4 4.7
3 x 2½ 80 x 65	3.500 88.9	2.875 73.0	2½ 64	1.5 0.7	8 x 5 200 x 125	8.625 219.1	5.563 141.3	3 76	11.6 5.3
4 x 1 100 x 25	4.500 114.3	1.315 33.4	3 76	2.2 1.0	8 x 6 200 x 150	8.625 219.1	6.625 168.3	4 102	11.9 5.4

Additional sizes available, see Gruvlok Catalog or contact an Anvil Representative.



For Listings/Approval Details and Limitations, visit our website at [www.anvilintl.com](http://www.anvilintl.com) or contact an Anvil® Sales Representative.

- Available galvanized.

## MATERIAL SPECIFICATIONS

### FABRICATED FITTINGS:

**1"-10"** Carbon Steel, Schedule 40, conforming to ASTM A-53, Grade B

**12" and above** Carbon Steel, Standard Wall, conforming to ASTM A-53, Grade B

### COATINGS:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

## PROJECT INFORMATION

## APPROVAL STAMP

<b>Project:</b>	<input type="checkbox"/> Approved
<b>Address:</b>	<input type="checkbox"/> Approved as noted
<b>Contractor:</b>	<input type="checkbox"/> Not approved
<b>Engineer:</b>	<b>Remarks:</b>
<b>Submittal Date:</b>	
<b>Notes 1:</b>	
<b>Notes 2:</b>	