


FIG. E-1 90° Elbow



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

E-1 90° ELBOW

Nominal Size	O.D.	Max. Working Pressure	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	Lbs./Kg
1	1.315	300	2¼	0.6
25	33.4	20.7	57	0.3
1¼	1.660	300	2¾	0.8
32	42.2	20.7	70	0.4
1½	1.900	300	2¾	1.1
40	48.3	20.7	70	0.5
2	2.375	300	3¼	1.5
50	60.3	20.7	83	0.7
2½	2.875	300	3¾	2.5
65	73.0	20.7	95	1.1
3 O.D.	2.996	300	3¾	2.9
76.1	76.1	20.7	95	1.3
3	3.500	300	4¼	4.2
80	88.9	20.7	108	1.9
4	4.500	300	5	6.7
100	114.3	20.7	127	3.0
5½ O.D.	5.500	300	5½	—
139.7	139.7	20.7	140	—
5	5.563	300	5½	11.9
125	141.3	20.7	140	5.4
6½ O.D.	6.500	300	6½	18.2
165.1	165.1	20.7	165	8.3
6	6.625	300	6½	17.3
150	168.3	20.7	165	7.9
8	8.625	300	7¾	32.2
200	219.1	20.7	197	14.6
10	10.750	300	9	54.1
250	273.1	20.7	229	24.5
12	12.750	300	10	70.0
300	323.9	20.7	254	31.8

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile Iron conforming to ASTM A-536

FINISH:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	