



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

E-2 45° ELBOW				
Nominal Size	O.D.	Max. Working Pressure	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	PSI/bar	In./mm	Lbs./Kg
1	1.315	300	1¾	0.5
25	33.4	20.7	44	0.2
1¼	1.660	300	1¾	0.8
32	42.2	20.7	44	0.3
1½	1.900	300	1¾	0.9
40	48.3	20.7	44	0.4
2	2.375	300	2	1.0
50	60.3	20.7	51	0.4
2½	2.875	300	2¼	1.8
65	73.0	20.7	57	0.8
3 O.D.	2.996	300	2¼	2.1
76.1	76.1	20.7	57	1.0
3	3.500	300	2½	2.5
80	88.9	20.7	64	1.1
4	4.500	300	3	4.7
100	114.3	20.7	76	2.2
5½ O.D.	5.500	300	3¼	—
139.7	139.7	20.7	83	—
5	5.563	300	3¼	11.6
125	141.3	20.7	83	5.2
6½ O.D.	6.500	300	3½	8.3
165.1	165.1	20.7	89	3.8
6	6.625	300	3½	11.6
150	168.3	20.7	89	5.2
8	8.625	300	4¼	17.9
200	219.1	20.7	108	8.1
10	10.750	300	4¾	30.0
250	273.1	20.7	121	13.6
12	12.750	300	5¼	40.4
300	323.9	20.7	133	18.3

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile Iron conforming to ASTM A-536

FINISH:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			