



For Listings/Approval Details and Limitations, visit our website at [www.anvilintl.com](http://www.anvilintl.com) or contact an Anvil® Sales Representative.

SK-1 GROOVED CAP			
Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	1¼	0.3
25	33.4	25	0.1
1¼	1.660	1	0.4
32	42.2	25	0.2
1½	1.900	1	0.5
40	48.3	25	0.2
2	2.375	1	0.7
50	60.3	25	0.3
2½	2.875	1	1.0
65	73.0	25	0.4
3 O.D.	3.000	1	0.9
76.1	76.1	25	0.4
3	3.500	1	1.5
80	88.9	25	0.7
4	4.500	1½	2.7
100	114.3	27	1.2
5	5.563	1½	4.4
125	141.3	27	2.0
6½ O.D.	6.500	1	5.5
165.1	165.1	25	2.5
6	6.625	1½	6.6
150	168.3	27	3.0
8	8.625	1¾	11.3
200	219.1	30	5.1
10*	10.750	1¼	21.0
250	273.1	32	9.5
12*	12.750	1¼	35.5
300	323.9	32	16.1

\*Supplied as Style K-1 only.

## MATERIAL SPECIFICATIONS

### CAST FITTINGS:

Ductile Iron conforming to ASTM-A536

### COATINGS:

- Rust inhibiting paint Color: ORANGE (standard) or
- Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
- Other available options: Example: RAL3000 or RAL9000 Series

PROJECT INFORMATION	APPROVAL STAMP
Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	