

Dimensions (In) - Loads (Lbs) - Weight (Lbs)

Туре	Bolt Size A	Max Load■	L	Н	W	Weight	Туре	Bolt Size A	Max Load ■	L	Н	W	Weight
	ln.	Lbs.	ln.	ln.	ln.	Lbs.		ln.	Lbs.	ln.	ln.	ln.	Lbs.
А	3/8	730	95/8	13/4	1½	1.33	В	5/8	2,160	12	3	1½	2.54
	1/2	1,350				1.43		3/4	3,230				2.82
	5/8	2,160				1.64	С	3/8	730	16	4	1½	3.10
	3/4	3,230				1.92		1/2	1,350				3.20
В	3/8	730	12	3	1½	2.23		5/8	2,160				3.41
	1/2	1,350				2.33		3/4	3,230				3.69

Note:

■ Based on the rod diameter only. Rating is subject to the conditions that the concrete used is of sufficient strength to hold the deck hanger.

Material Specifications

Size Range

3/8" through 3/4"

Material

Carbon steel

Finish

Plain

Service


Recommended for suspending pipe or conduit in metal concrete deck forms for a variety of rod sizes. May be used with a rod coupling such as the Fig. 135 or 136 to allow for extended rod lengths.

Features

- L and H can be specified for a custom fit if your particular deck does not accommodate type A, B, or C.
- Standard 6" long UNC bolt is welded to bracket to ensure assembly remains intact during shipment.

Ordering

Specify Figure 284, design type (A, B, C) and bolt diameter. If your specific deck will not fit one of the design types and/or a different bolt size is required, specify leg height (H), opening (L) and bolt size.



Before pouring concrete, locate the Figure 284 on deck so legs rest in "valleys" of form. Drill hole in deck for bolt.



PROJECT INFORMATION	APPROVAL STAMP			
Project:	Approved			
Address:	Approved as noted			
Contractor:	Not approved			
Engineer:	Remarks:			
Submittal Date:				
Notes 1:				
Notes 2:				