

## Class 125 (Standard) Fig. 3358 Straight Tee



For Listings/Approval Details and Limitations, visit our website at [www.asc-es.com](http://www.asc-es.com) or contact an ASC Engineered Solutions™ Sales Representative.

### Material Specifications

**Dimensions:** ASME B16.4 Class 125

**Material:** ASTM A126


**Finish:** Black or Hot Dip Galvanized per ASTM A153 Class A

**Threads:** NPT per ASME B1.20.1

**Agency Approvals:** All cast iron threaded fittings are UL/ULC Listed and FM Approved.

**Figure 3358** Straight Tee

Nominal Size	Maximum Working Pressure ▲	Dimension A	Approx. Wt. Each
In. (mm)	psi (kPa)	In. (mm)	Lbs. (kg)
1	300	1.50	1.21
25	2065	38.10	0.55
1¼	300	1.75	1.87
32	2065	44.45	0.85
1½	300	1.94	2.51
40	2065	49.27	1.14
2	300	2.25	3.96
50	2065	57.15	1.80
2½	300	2.70	6.45
65	2065	68.58	2.93



▲ - Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit [asc-es.com](http://asc-es.com) or contact your local ASC Engineering Solutions™ Representative.



PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	