

Dimensions (In) - Weight (Lbs)

Rod Size A	В	D	Weights				Length
			41/2	8	10	14	L
In.	ln.	In.	Lbs.	Lbs.	Lbs.	Lbs.	In.
3/8	1	7/16	0.17	0.28	0.35	0.53	4½, 8, 10, 14
1/2	1 1/4	15/32	0.22	0.37	0.46	0.63	
5/8	13/8	11/16	0.25	0.43	0.51	0.73	
3/4							

Material Specifications

Size Range

3/8" through 1/2"

Material

Carbon steel

Finish

Plain

Zinc Plated (Hot-Dip Galvanized optional)

Service

For use with Figs. 86, 88 & 95. NOT for seismic applications.

How to size

Specify length of retaining strap based on beam size.


Installation

Length of strap should be adequate to allow at least 1" of strap to be bent over the beam side of the flange opposite the side the beam clamp is mounted on.

Ordering

Specify rod size, figure number, name, length of retaining clip and finish (Add 2" to flange width of beam to arrive at proper length of retaining clip).

If required length is not standard, order next longer standard.





PROJECT INFORMATION	APPROVAL STAMP	
Project:	Approved	
Address:	Approved as noted	
Contractor:	Not approved	
Engineer:	Remarks:	
Submittal Date:		
Notes 1:		
Notes 2:		